

Safe Series™

300kA/400kA

Industrial Surge Protection



- Dimensions
19" L x 14 3/4" W x 6 1/2" D
- Weight
79 lbs.



Sycom announces another truly remarkable breakthrough in surge protection technology. In keeping with the highest quality surge protection devices **Sycom** takes pride in introducing their new line of industrial surge protectors. The thermal protection with matched components is unbeatable in the market today.

Features:

- UL/cUL 1449-2009
- Designed and tested to ANSI/IEEE C62.11, C62.41, and C62.45
- Listed for UL96A Lightning Protection
- Type 2 SPD
- SCCR Rating 65,000A
- Response Time: < 5 ns.
- Protection Modes, all modes (L-N, L-G, N-G, L-L)
- Operating Frequency: 47-63Hz
- Enclosure NEMA 12 standard
- Nominal Discharge (In): 20kA
- Component Level Fusing
- Temperature -40 to +60 C
- Thermal Protection
- 3 Way Diagnostic Lights
- Connection Method:
 - Parallel
 - Lug connection accepts 4AWG – 14AWG Wire
- Available Options:
 - Form C Contacts
 - Surge Counter
 - Audible Alarm
 - Fused Disconnect
 - Wiring Harness
 - RFI/EMI Filtering



Sycom Surge, Inc.
12929 44th St N
Clearwater, FL 33762
Tel: (727)561-7697 Fax: (727) 556-0182
Toll Free (800) 622-9904
Visit our Web Site
www.sycomsurge.com